



Technical Bulletin

BULLETIN NO.	110-02
ISSUED:	March 15, 2006
REPLACES:	April 15, 2004

Material Safety Data Sheet (MSDS)

Plasti-Fab expanded polystyrene (EPS) products for construction applications are made from raw materials containing combustion modifier.

Section 1: Product Information & Company Identification

Products: PlastiSpan[®] insulation, PlastiSpan EFS insulation, PlastiSpan HD insulation, GeoDrain[®] foundation insulation board, DuroFoam[®] insulation board, Advantage ICF System[®], GeoSpec lightweight fill material, GeoSpan[®] compressible fill material and GeoVoid[®] compressible fill material.

Synonyms: Expanded Polystyrene (EPS) foam plastic insulation

Product Grades: CAN/ULC-S701, Types 1, 2 & 3 and ASTM C578, Types I, II, VIII & IX

Chemical Family: Ethenylbenzene Homopolymer

Formula: (C₈H₈)_n

TSCA Inventory Status: Listed

Supplier Corporate Office:

Plasti-Fab Ltd.
 #270, 3015 - 5th Avenue N.E.
 Calgary, Alberta T2A 6T8
 Health Issues Information (8:00 AM to 5:00 PM MT): (403) 248-9306
 Technical Information: 1-888-446-5377

Section 2: Composition/Ingredients

<u>Component:</u>	<u>CAS Registry No:</u>	<u>Approx. Weight Percentage:</u>
Pentane	109-66-0	0 to 1% amounts rapidly decreasing with age
Flame Retardant	3322-93-8	0.9% max.
Coatings	N/A	0.5% max.
Polystyrene Thermoplastic	9003-53-6	98 to 99%

Component Related Regulatory Information:

This product may be regulated, have exposure limits or other information identified as the following:
 Nuisance particulates.

Component Information/Information on Non-Hazardous Components:

No additional information available.

Section 3: Health Hazards

PRINCIPAL HEALTH HAZARDS, SIGNS & SYMPTOMS OF EXPOSURE:

Eye Contact: Dust or particles in eyes may cause mechanical eye irritation and/or injury.

Inhalation: Dust from mechanical fabrication may cause upper respiratory tract irritation. Fumes from hot wire cutting can also cause upper respiratory tract irritation (see also section 8 of this MSDS).

Skin Contact: Irritation from skin contact is rare. In a few individuals, contact may produce slight skin irritation.

Ingestion: Product is biologically inert. If swallowed, it may act as an obstruction.

Incompatibility (Materials to avoid): Product will dissolve in most organic solvents, and some insecticides, aldehydes and amines.

Section 4: First Aid

Eyes: If dust or particles become lodged in eyes, rinse with clean water. Obtain medical attention if condition is painful.

Inhalation: If overcome by exposure, remove individual to fresh air. If symptoms persist provide oxygen and obtain medical attention.

Skin: Contact is not expected to present a skin hazard. Wash exposed areas with mild soap and water. Consult physician if irritation persists.

Ingestion: Product is not expected to present significant ingestion hazard. If it does occur, watch the person for several days to make sure obstruction does not occur. Do not induce vomiting unless directed to by physician.

Section 5: Physical Data

Form: Products consist of rigid cellular foam blocks, boards and shapes.

Colour: White, green tint or brown tint

Odour: Very slight hydrocarbon odour

Boiling Point: N/A

Melting Point: Softens at 70 to 80 °C (160 to 176 °F)

Specific Gravity: (water = 1): 0.6 to 2.0

Vapour Pressure: N/A

Volatile by Volume: <4% (pentane and water)

Vapour Density (Air = 1): N/A

Evaporation Rate: None

Solubility in Water: Insoluble

Section 6: Fire & Explosion

Flash Point: >345 °C (>650 °F) using ASTM Test Method D1929

Special Fire Fighting Instructions: Fire fighters should wear self-contained breathing apparatus and personal protective clothing (turn out gear) in a sustained fire.

Extinguishing Media: Water fog, carbon dioxide, dry chemical, foam should be used.

Auto-ignition Temperature: 440 °C (824 °F) Min.

Usual Fire and Explosion Hazards: Burning may produce dense black smoke. Smoke consists of carbon monoxide, carbon dioxide, styrene, hydrogen halide, nuisance particulate, carbon (soot) and pentane. Other undetermined hydrocarbon fractions could be released in trace quantities. Dust generated by fabrication (i.e., sanding, sawing, etc.) will increase fire hazard and should be handled accordingly.

Section 7: Reactivity Data

Stability (Conditions to avoid): Product is stable. However, exposure to fire and high temperatures must be avoided.

Incompatibility (Materials to avoid): Product will dissolve in hydrocarbons, esters, aldehydes and amines.

Hazardous Decomposition: Primary combustion products include carbon monoxide, carbon dioxide, styrene, hydrogen halide, nuisance particulate, carbon (soot) and pentane. Other undetermined hydrocarbon fractions could be released in trace quantities.

Hazardous Polymerization: Will not occur.



MSDS

Technical Bulletin 110-02

Page 3 of 3

Section 8: Exposure Controls/Personal Protection

General Control Measures for Hot-Wire Cutting:

Provide sufficient general and/or local exhaust ventilation to maintain exposure below permissible personal exposure limit (PEL) or threshold limit value (TLV) for combustion products from hot wire cutting. Use local exhaust, where possible, in confined or enclosed spaces. Wear approved safety glasses/goggles and dust mask if mechanical fabrication is to take place.

Personal Protective Equipment:

Respiratory Protection: Use approved dust mask when sawing or sanding. Use approved NIOSH respirator when the PEL or TLV for combustion products from hot wire cutting, sawing or sanding may be exceeded.

Skin Protection: Skin protection not normally required. Wear gloves and/or sleeves, if sensitivity noted.

Eye Protection: Use approved safety glasses/goggles when sawing or sanding.

Section 9: Spill or Leak Procedures

Spill, Leak or Release Procedures: Normal good housekeeping should be observed. Material can be swept or picked up and placed into a suitable container for disposal.

Reportable Quantity: None.

Disposal Method: Recycle, incinerate (WTE) or landfill per local and provincial regulations.

Section 10: Disposal Considerations

General Product Information: Material, if discarded, is not expected to be a characteristic hazardous waste.

Disposal Instructions: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 11: Transportation Information

Shipping Name: Not regulated for transport.

Hazard Class: None

UN/NA #: None

Packing Group: None

Section 12: Special Precautions

Storage and Handling: Although expanded polystyrene contains a fire retardant additive, it is considered combustible and adequate protection from sources of ignition should be taken.

Combustibility Labelling:

CAUTION: THIS PRODUCT IS COMBUSTIBLE. A PROTECTIVE BARRIER OR THERMAL BARRIER IS REQUIRED AS SPECIFIED IN THE APPROPRIATE BUILDING CODE".

Section 13: MSDS INFORMATION

The information contained herein is provided as a general reference. Plasti-Fab Ltd. believes the data set forth herein to be accurate and the information is given in good faith. Plasti-Fab Ltd. makes no guarantee or warranty and does not assume any liability with respect to the accuracy or completeness of such information.

Prepared for:
Plasti-Fab Ltd.
270, 3015 - 5th Avenue N.E.
Calgary, Alberta T2A 6T8
Phone: (403) 248-9306

Prepared by:
W. James Whalen, P.Eng.
Technical Marketing Manager
Plasti-Fab Ltd.

Date Issued: March 15, 2006

Replaces: April 15, 2004