

Product Information Bulletin

BULLETIN NO.	237
ISSUED:	July 18, 2017
REPLACES:	December 8, 2016

US Product Certification Listings for Plasti-Fab® Insulation

PlastiSpan®, **DuroSpan™** and **ENERGREEN®** insulation are listed with Intertek Testing Services NA, Ltd. for material properties in accordance with in accordance with ASTM C578, **Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation**, and for surface burning characteristics in accordance with ASTM E84, **Standard Test Method for Surface Burning Characteristics of Building Materials**.

The Intertek certification marks below are used on labels and/or packaging to signify third party certification/quality control of Plasti-Fab EPS insulation in accordance with ASTM C578 and ASTM E84.

Current Intertek Certification Mark	Transitioning to ETL Mark Prior to 12/31/2020
 Intertek	 Intertek

Material Details		Index	
ASTM C578 Types	Thickness	Flame Spread	Smoke Developed
I, VIII, II, IX, XIV and XV	Max. 6 inches	20	300

Notes:

1. See Plasti-Fab Product Information Bulletin #'s 208 (**PlastiSpan** insulation), 247 (**DuroSpan** insulation) and 308 (**ENERGREEN** insulation) for material properties as per ASTM C578.
2. See ICC-ES Evaluation Report ESR-1587 for **PlastiSpan** Insulation compliance with requirements of the International Building Code (IBC) and International Residential Code (IRC).
3. See Intertek Code Compliance Research Report CCRR-1072 for **PlastiSpan**, **DuroSpan** and **ENERGREEN** insulation compliance with requirements of the IBC, IRC and National Building Code of Canada.